JJMICROELECTRONICS

! □! 2□ ! A T R V A h VcEcV T D76E

JMTL84K

Features

- Excellent $R_{DS(ON)}$ and Low Gate Charge
- Halogen-free; RoHS-compliant
- Pb-free plating

Applications

- Load Switch
- PWM Application
- Power Management

Product Summary

Parameters	Value	Unit
V_{DSS}	-50	V
$V_{GS(th)_Typ}$	-1.4	V
I_D(@V_{GS}=10V)	-0.44	A
$R_{DS(ON)_Typ}$(@V_{GS}=-10V)	2.0	Ω
$R_{DS(ON)_Typ}$(@V_{GS}=-4.5V)	2.1	Ω



SOT-23 Top View



Pin Assignment



Schematic Diagram

Ordering Information

Device	Marking	MSL	Form	Package	Reel(pcs)	Per Carton (pcs)
JMTL84K	B84K	3	Tape&Reel	SOT-23	3000	120000

Absolute Maximum Ratings (@ T_A = 25°C unless otherwise specified)

Symbol	Parameter		Value	Unit
V_{DS}	Drain-to-Source Voltage		-50	V
V_{GS}	Gate-to-Source Voltage		±20	V
I_D	Continuous Drain Current	T_A = 25°C	-0.44	A
		T_A = 100°C	-0.28	
I_{DM}	Pulsed Drain Current [1]		Refer to Fig.4	A
P_D	Power Dissipation	T_A = 25°C	1.0	W
		T_A = 100°C	0.4	
T_J, T_{STG}	Junction & Storage Temperature Range		-55 to 150	°C

Thermal Characteristics

Symbol	Parameter	Max	Unit
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient[2]	131	

All product information is copyrighted and subject to legal disclaimers.

Electrical Characteristics (T_J = 25°C unless otherwise specified)

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
Off Characteristics						
$V_{(BR)DSS}$	Drain-Source Breakdown Voltage	I_D = -250μA, V_{GS} = 0V	-50	-	-	V
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS} = -50V, V_{GS} = 0V	-	-	-1.0	μA
I_{GSS}	Gate-Body Leakage Current	V_{DS} = 0V, V_{GS} = ±20V	-	-	±10	μA
On Characteristics						
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS} = V_{GS}, I_D = -250μA	-1.0	-1.4	-1.9	V
$R_{DS(ON)}$	Static Drain-Source ON-Resistance(3)	V_{GS} = -10V, I_D = -0.13A	-	2.0	2.6	Ω
		V_{GS} = -4.5V, I_D = -0.1A	-	2.1	3.6	Ω
Dynamic Characteristics						
R_g	Gate Resistance	f = 1MHz	-	154	-	Ω
C_{iss}	Input Capacitance	V_{GS} = 0V, V_{DS} = -25V, f = 1MHz	-	55	82	pF
C_{oss}	Output Capacitance		-	13	-	pF
C_{rss}	Reverse Transfer Capacitance		-	6.7	-	pF
Q_g	Total Gate Charge	V_{GS} = 0 to -10V, V_{DS} = -25V, I_D = -2A	-	1.7	-	nC
Q_{gs}	Gate Source Charge		-	0.5	-	nC
Q_{gd}	Gate Drain("Miller") Charge		-	0.3	-	nC
Switching Characteristics						
$t_{d(on)}$	Turn-On DelayTime	V_{GS} = -10V, V_{DD} = -25V, I_D= -2A, R_{GEN} = 3Ω	-	2	-	ns
t_r	Turn-On Rise Time		-	2	-	ns
$t_{d(off)}$	Turn-Off DelayTime		-	16	-	ns
t_f	Turn-Off Fall Time		-	12	-	ns
Body Diode Characteristics						
I_S	Maximum Continuous Body Diode Forward Current		-	-	-0.4	A
I_{SM}	Maximum Pulsed Body Diode Forward Current		-	-	-1.8	A
V_{SD}	Body Diode Forward Voltage	V_{GS} = 0V, I_S = -0.13A	-		-1.2	V
trr	Body Diode Reverse Recovery Time	I_F = -2A, di/dt = 100A/us	-	22	-	ns
Qrr	Body Diode Reverse Recovery Charge		-	16	-	nC

Notes: 1. Repetitive Rating: Pulse Width Limited by Maximum Junction Temperature.

2. $R_{\theta JA}$ is measured with the device mounted on FR-4 substrate PC board, 2oz copper, with 1inch square pad layout.

3. Pulse Test: Pulse Width≤300μs, Duty Cycle≤0.5%.

Typical Performance Characteristics

Figure 1: Power De-rating



Figure 2: Current De-rating



Figure 3: Normalized Maximum Transient Thermal Impedance



t, Rectangular Pulse Width (s)

Figure 4: Peak Current Capacity



t, Rectangular Pulse Width (s)

Typical Performance Characteristics



Typical Performance Characteristics

Figure 11: Normalized Breakdown voltage vs. Junction Temperature



Figure 12: Normalized on Resistance vs. Junction Temperature





Test Circuit



Figure 1: Gate Charge Test Circuit & Waveform



Figure 2: Resistive Switching Test Circuit & Waveform



Figure 3: Unclamped Inductive Switching Test Circuit& Waveform



Figure 4: Diode Recovery Test Circuit & Waveform

All product information is copyrighted and subject to legal disclaimers.

Package Mechanical Data(SOT-23)

Package Outline



Recommended Footprint



Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co.,Ltd assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.
Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information.

is a registered trademark of Jiangsu JieJie Microelectronics Co.,Ltd.