JOCHC15B-D8P/S Series

Rev.A.1.0

DESCRIPTION:

The products are 15MBd high-speed opto-couplers in a plastic DIP8 package with different lead forming options. The device consists of a 850 nm AlGaAS LED, optically coupled to a very high speed integrated photo-detector logic gate with a strobable output. The output end of the product is a CMOS output, and the product has a strong common mode rejection capability. The coupled parameters are guaranteed over the temperature range of -40°C to +110°C. The products are widely used in communication interface, digital isolation for A/D, D/A conversion, high-voltage power systems, renewable energy inverters, medical imaging and patient monitoring.



MAIN FEATURES

High isolation 5000 VRMS
High speed – 15MBd typical
Operating temperature range -40°C to 110°C
REACH & RoHS compliance
HBM: H3A; MM: M4; CDM: C3
CQC approved
VDE approved
UL approved

Truth Table

LED	Output
ON	L
OFF	H

ABSOLUTE MAXIMUM RATINGS (Temperature=25°C)

Parameter		Symbol	Value	Unit
Input	Forward Current	I_F	50	mA
	Peak Forward Current	I_{FP}	1	A
	Reverse Voltage	V_R	6	V

	Input Power Dissipation	P_D	100	mW
Output	Supply Voltage	V_{CC}	7	V
	Output Voltage	V_O	V_{CC}+0.5	V
	Output Current	I_O	10	mA
	Output Power Dissipation	P_O	22	mW
Total Power Dissipation		P_{tot}	130	mW
Isolation Voltage		V_{iso}	5000	Vrms
Operating Temperature		T_{opr}	-40~110	
Junction Temperature		T_j	125	
Storage Temperature		T_{stg}	-55~125	
Soldering Temperature		T_{sol}	260	

NOTE1 μ

NOTE2

ELECTRICAL CHARACTERISTICS (Temperature=25°C)

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit

S E

	Propagation Delay Time to Logic Low	TPHL	I_F=7mA,C_L=15pF	-	70	100	ns
	Propagation Delay Time to Logic High	TPLH	I_F=7mA,C_L=15pF	-	55	100	ns
	Common Mode Transient Immunity at Logic High	CM_H	I_F=0mA, V_{CM}=1000Vpp, C_L=15pF, V_{CC}=5V	20	-	-	kV/μs
	Common Mode Transient Immunity at Logic Low	CM_L	I_F=7mA, V_{CM}=1000Vpp, C_L=15pF, V_{DD}=5V	20	-	-	kV/μs

Recommended Operating Conditions

Characteristics	Symbol	Min.	Typ.	Max.	Unit
Operating Temperature	T_a	-40	-	105	
Supply Voltage	V_{CC}	2.7	-	5.5	V
Low Level Input Current	I_{FL}	0	-	250	μA
High Level Input Current	I_{FH}	8	-	16	mA
Forward Voltage	$V_{F(OFF)}$	-	-	0.8	V

ORDERING INFORMATION



Packing Quantity			
Option	**Quantity**	**Quantity – Inner box**	**Quantity –Outer box**

MARKING





Characteristics Curves

FIG.1: Forward Current vs. Forward Voltage

FIG.2: Max. Allowable LED Forward Current vs. Ambient Temperature

FIG.7: Propagation Delay vs. Ambient Temperature



FIG.8: Propagation Delay vs. Ambient Temperature

Fig.10: CMTI Test Circuit Recommendations



Package Dimension (Unit: mm)

Standard DIP Type:



Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	6.20		6.60	0.244		0.260
B	9.40		9.80	0.370		0.386
C	7.15		8.95	0.281		0.352
D	3.20		3.60	0.126		0.142
E	7.32		7.92	0.288		0.312
F	0.15		0.35	0.006		0.014
G	0.90		1.50	0.035		0.059
H	3.90		4.50	0.154		0.177
I	0.40		0.60	0.016		0.024
J	2.29		2.79	0.090		0.110
K	2.24		3.24	0.088		0.128

Option SMD Type:



Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	6.20		6.60	0.244		0.260
B	9.40		9.80	0.370		0.386
C	9.50		10.50	0.374		0.413
D	3.20		3.60	0.126		0.142
E	7.32		7.92	0.288		0.312
F	0.05		0.35	0.002		0.014
G	0.16		0.36	0.006		0.014
H				0 ŏẘ	0.	4
I	0.90		1.50	0.035		0.059
J	3.30		3.90	0.130		0.154
K						

RECOMMENDED SOLDER MASK (Dimensions in mm unless otherwise stated)



TUBE SPECIFICATIONS (Dimensions in mm unless otherwise stated)

Standard DIP



CARRIER TAPE SPECIFICATIONS (Dimensions in mm unless otherwise stated)

Option S



Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
D0		1.50	1.60		0.059	0.063
P0	3.90	4.00	4.10	0.154	0.157	0.161
P1	11.90	12.00	12.10	0.469	0.472	0.476
P2	1.90	2.00	2.10	0.075	0.079	0.083
E	1.65	1.75	1.85	0.065	0.069	0.073
F	7.40	7.50	7.60	0.291	0.295	0.299
T	0.35	0.40	0.45	0.014	0.016	0.018
W	15.90	16.00	16.20	0.626	0.630	0.638

REFLOW INFORMATION



Profile Feature	Sn-Pb Assembly Profile	Pb-Free Assembly Profile
Temperature Min. (Tsmin)	100	150
Temperature Max. (Tsmax)	150	200
Time (ts) from (Tsmin to Tsmax)	60-120 seconds	60-120 seconds
Ramp-up Rate (tL to tP)	3 /second max.	3 /second max.
Liquidus Temperature (TL)	183	217
Time (tL) Maintained Above (TL)	60-150 seconds	60-150 seconds
Peak Body Package Temperature	235 +0 /-5	260 +0 /-5
Time (tP) within 5 of 260	10 seconds	10 seconds
Ramp-down Rate (TP to TL)	3-6 /second	3-6 /second
Time 25 to Peak Temperature	6 minutes max.	8 minutes max.

WAVE SOLDERING



HAND SOLDERING BY SOLDERING IRON	
Soldering Temperature	360 5
Soldering Time	3s max.

Note:

1. Reflow soldering is recommended at the temperatures and times shown, no more than three times.

2. Avoid direct contact between the epoxy body and any tools or surfaces exceeding its maximum storage temperature.

3. Application of pressure on the epoxy body is prohibited at elevated temperatures. In specific scenarios, any applied force must not exceed 2.5N.

4. Ensure the component has cooled to ambient temperature before proceeding with any subsequent manufacturing steps.

5. The component has a shelf life of one year when stored under standard conditions.

6. Recommend storage Temp.: 0~40°C;

Recommend storage humidity: <60%;

MSL level: MSL 1

Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document supersedes and replaces all information previously supplied.

is a registered trademark of Jiangsu JieJie Microelectronics Co., Ltd.

Copyright © 2026 Jiangsu JieJie Microelectronics Co., Ltd. All rights reserved.