JJMICROELECTRONICS

1200V 40A Trench and Field Stop IGBT

JJT40N120HE

Key performance:

- V_{CE} =1200V
- I_C=40A@T_C=100
- $V_{CE(sat)}$=1.9V

TO-247





Features:

- Trench and field-stop technology
- High speed switching
- Low collector to emitter saturation voltage
- Easy parallel switching capability
- High ruggedness performance
- RoHS compliant

Applications:

- Welding machines
- UPS
- Solar inverters

Package parameters

Type	Marking	Package	Packaging Method
JJT40N120HE	T40120HE	TO-247	Tube

All product information is copyrighted and subject to legal disclaimers.

Maximum ratings

Symbol	Parameter	Values	Unit
V_{CES}	Collector-emitter voltage	1200	V
V_{GES}	Gate-emitter voltage	±20	V
I_C	Continuous collector current (T_C=25)	80	A
	Continuous collector current (T_C=100)	40	A
I_{CM}	Pulsed collector current, t_p limited by T_{vjmax}	160	A
I_F	Diode continuous forward current (T_C=100)	40	A
I_{FM}	Diode maximum current, t_p limited by T_{vjmax}	160	A
P_{tot}	Power dissipation (T_C=25)	395	W
	Power dissipation (T_C=100)	197	W
T_{vj}	Operating junction temperature range	-40 to +175	
T_{stg}	Storage temperature range	-55 to +150	

Thermal characteristics

Symbol	Parameter	Values		Unit
		Typ.	Max.	
$R_{th(j-c)}$	Thermal resistance, junction to case for IGBT	-	0.38	K/ W
$R_{th(j-c)}$	Thermal resistance, junction to case for Diode	-	0.65	K/ W
$R_{th(j-a)}$	Thermal resistance, junction to ambient	-	40	K/ W

All product information is copyrighted and subject to legal disclaimers.

Electrical characteristics of IGBT (T_{vj}=25 unless otherwise specified)

Static characteristics

Symbol	Parameter	Test condition	Values			Unit
			Min.	Typ.	Max.	
BV_{CES}	Collector-emitter breakdown voltage	V_{GE}=0V, I_C=250μA	1200	-	-	V
I_{CES}	Collector-emitter leakage current	V_{CE}=1200V, V_{GE}=0V	-	-	100	μA
I_{GES}	Gate leakage current, forward	V_{GE}=20V, V_{CE}=0V	-	-	100	nA
	Gate leakage current, reverse	V_{GE}=-20V, V_{CE}=0V	-	-	-100	nA
$V_{GE(th)}$	Gate-emitter threshold voltage	V_{GE}=V_{CE}, I_C=1mA	5.0	6.0	7.0	V
$V_{CE(sat)}$	Collector-emitter saturation voltage	V_{GE}=15 V, I_C=40A	-	1.9	-	V
		V_{GE}=15V, I_C=40A, T_{vj}=175	-	2.2	-	V

Dynamic characteristics

Symbol	Parameter	Test condition	Values			Unit
			Min.	Typ.	Max.	
C_{ies}	Input capacitance	V_{CE}=30V V_{GE}=0V f=1MHz	-	9900	-	pF
C_{oes}	Output capacitance		-	189	-	pF
C_{res}	Reverse transfer capacitance		-	40	-	pF
Q_g	Total gate charge	V_{CC}=960V V_{GE}=15V I_C=40A	-	263	-	nC

All product information is copyrighted and subject to legal disclaimers.

Switching characteristics

Symbol	Parameter	Test condition	Values			Unit
			Min.	Typ.	Max.	
$t_{d(on)}$	Turn-on delay time	V_{CC}=600V V_{GE}=0/15V I_C=40A R_G=10Ω Inductive load	-	85	-	ns
t_r	Rise time		-	76	-	ns
$t_{d(off)}$	Turn-off delay time		-	307	-	ns
t_f	Fall time		-	69	-	ns
E_{on}	Turn-on energy		-	2.5	-	mJ
E_{off}	Turn-off energy		-	1.4	-	mJ
E_{ts}	Total switching energy		-	3.9	-	mJ
$t_{d(on)}$	Turn-on delay time	V_{CC}=600V V_{GE}=0/15V I_C=40A R_G=10Ω Inductive load T_{vj}=175	-	76	-	ns
t_r	Rise time		-	75	-	ns
$t_{d(off)}$	Turn-off delay time		-	360	-	ns
t_f	Fall time		-	149	-	ns
E_{on}	Turn-on energy		-	2.9	-	mJ
E_{off}	Turn-off energy		-	2.6	-	mJ
E_{ts}	Total switching energy		-	5.5	-	mJ

All product information is copyrighted and subject to legal disclaimers.

Electrical characteristics of Diode (T_{vj}=25 unless otherwise specified)

Symbol	Parameter	Test condition	Values			Unit
			Min.	Typ.	Max.	
V_F	Diode forward voltage	I_F=40A	-	2.0	-	V
		I_F=40A T_{vj}=175	-	1.6	-	V
t_{rr}	Diode reverse recovery time	V_R=600V I_F=40A di_F/dt=-750A/μs	-	175	-	ns
I_{rrm}	Diode peak reverse recovery current		-	24	-	A
Q_{rr}	Diode reverse recovery charge		-	2000	-	nC
t_{rr}	Diode reverse recovery time	V_R=600V I_F=40A di_F/dt=-750A/μs T_{vj}=175	-	285	-	ns
I_{rrm}	Diode peak reverse recovery current		-	37	-	A
Q_{rr}	Diode reverse recovery charge		-	5500	-	nC

All product information is copyrighted and subject to legal disclaimers.

Typical performance characteristics



Fig 1. Typical output characteristic (T_{vj}=25)



Fig 2. Typical output characteristic(T_{vj}=175)



Fig 3. Power dissipation as a function of T_C



Fig 4. Typical Gate charge



Fig 5. Typical $V_{GE(th)}$ as a function of T_{vj} (I_C=1mA)



Fig 6. Typical V_F as a function of T_{vj}

All product information is copyrighted and subject to legal disclaimers.

Typical performance characteristics



Fig 7. Typical V_{CEsat} as a function of T_{vj}



Fig 8. Typical I_F as a function of V_F



Fig 9. Typical switching time as a function of I_C



Fig 10. Typical switching times as a function of R_G



Fig 11. Typical switching energy losses as a function of I_C



Fig 12. Typical switching energy losses as a function of R_G

All product information is copyrighted and subject to legal disclaimers.

Typical performance characteristics



Fig 13. Typical capacitance as a function of V_{CE} (f=1Mhz, V_{GE}=0V)



Fig 14. Transient thermal impedance of IGBT

All product information is copyrighted and subject to legal disclaimers.

Package dimension

TO-247



Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	15.50	15.80	16.10	0.610	0.622	0.634
B	20.80	21.00	21.20	0.819	0.827	0.835
C	19.70	20.00	20.30	0.776	0.787	0.799
D	1.80	2.00	2.20	0.071	0.079	0.087
E	1.90	2.10	2.30	0.075	0.083	0.091
F	1.00	1.20	1.40	0.039	0.047	0.055
G	5.25	-	5.65	0.207	-	0.222
H	4.80	5.00	5.20	0.189	0.197	0.205
J	1.90	2.00	2.10	0.075	0.079	0.083
K	2.20	2.35	2.50	0.087	0.093	0.098
L	0.41	0.60	0.79	0.016	0.024	0.031
M	2.80	3.00	3.20	0.110	0.118	0.126
N	2.90	3.10	3.30	0.114	0.122	0.130

All product information is copyrighted and subject to legal disclaimers.

Revision history

Date	Revision	Changes
2023-12-12	Rev. 1.0	Release of the datasheet.
2024-04-03	Rev. 1.1	Update
2024-05-17	Rev. 1.2	Update
2026-06-25	Rev 1.3	Update thermal

Disclaimer

PLEASE NOTE - Jiangsu JieJie Microelectronics Co., Ltd ("JJM") reserves the right to amend, correct, modify and enhance the product and/or this document at any time without prior notice. If you intend to purchase this product, please obtain the latest information available before placing your order. The sale of JJM products is governed by JJM's prevailing terms and conditions at the time of purchase and purchasers are solely responsible for the selection and use of the products with no liability on JJM's part to supply application assistance or customization. Purchase of JJM products does not grant the purchaser license, express or implied, to JJM's intellectual property. Any warranties provided with JJM products are null and void upon resale unless accompanied by the information set forth herein in its entirety. The JJM name and logo are registered trademarks of Jiangsu JieJie Microelectronics Co., Ltd. This document supersedes all previous versions. ©2026 JJM - All rights reserved